according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 01, 2022

1 Identification

· Product identifier

· Trade name: Gel Chafing Fuel

· Product code: M200/M200-12

· Other means of identification: Blue Magic Gel

· Recommended use and restriction on use

· Recommended use:

Maintaining acceptable serving temperatures in buffet dishes containing warm, cooked food. • **Restrictions on use:** No relevant information available.

• Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier: Pico Inc. 71 Whitmore Road Vaughan Ontario Canada L4L 8G5 1-800-267-6428

· Emergency telephone number:

ChemTel Inc.

(800) 255-3924 (North America)

(801) 1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Sol. 1 H228 Flammable solid.
Acute Tox. 3 H301 Toxic if swallowed.
Acute Tox. 3 H311 Toxic in contact with skin.
Acute Tox. 3 H331 Toxic if inhaled.
Eye Irrit. 2B H320 Causes eye irritation.
STOT SE 1 H370 Causes damage to the central nervous system and optic nerve.

[·] Label elements

 • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
 • Hazard pictograms:



 Signal word: Danger
 Hazard statements: H228 Flammable solid. H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled. H320 Causes eye irritation. H370 Causes damage to the central nervous system and optic nerve.
 Precautionary statements:

(Cont'd. on page 2)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 25, 2019

Trade name: Gel Chafing Fuel (Cont'd. of page 1) Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P210 P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting/equipment. P260 Do not breathe dust/fume/gas/mist/vapors/spray. P264 Wash thoroughly after handling. P270 Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. P271 P280 Wear protective gloves/protective clothing/eye protection. If swallowed: Immediately call a poison center/doctor. P301+P310 P330 Rinse mouth. If on skin: Wash with plenty of water. P302+P352 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. P312 P337+P313 If eye irritation persists: Get medical advice/attention. P361+P364 Take off immediately all contaminated clothing and wash it before reuse. In case of fire: Use for extinction: CO2, powder or water spray. P370+P378 P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. • Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:

67-56-1 Methanol

🚸 Flam. Liq. 2, H225	50-100%
💑 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331	
🕉 STOT SE 1, H370	
Ěye Irrit. 2B, H320	

· Additional information:

For the wording of the listed Hazard Statements, refer to section 16. For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

[•] Description of first aid measures

• After inhalation:

Supply fresh air or oxygen; call for doctor.

Provide oxygen treatment if affected person has difficulty breathing.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

(Cont'd. on page 3)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 25, 2019

Trade name: Gel Chafing Fuel

(Cont'd. of page 2) Remove contact lenses if worn. Rinse opened eye for several minutes under running water. Then consult a doctor. · After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; immediately call for medical help. Most important symptoms and effects, both acute and delayed: Headache Thirst Dizziness Nausea Acidosis Disorientation Unconsciousness Danger: Danger of circulatory collapse. Danger of convulsion. Danger of impaired breathing. Indication of any immediate medical attention and special treatment needed: Monitor circulation, possible shock treatment. If necessary oxygen respiration treatment.

5 Fire-fighting measures

• Extinguishing media

• Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: None.

- Special hazards arising from the substance or mixture No relevant information available.
- Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

• Additional information: Cool endangered receptacles with water spray.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

• Environmental precautions Avoid release to the environment.

Methods and material for containment and cleaning up

Absorb liquid components with non-combustible liquid-binding material.

Towel or mop up material and collect in a suitable container.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Cont'd. on page 4)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 25, 2019

Trade name: Gel Chafing Fuel

(Cont'd. of page 3)

See Section 13 for disposal information.

7 Handling and storage

• Handling

· Precautions for safe handling:

Store in cool, dry place in tightly closed receptacles.

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

- Open and handle receptacle with care.
- Keep out of reach of children.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

[•] Conditions for safe storage, including any incompatibilities

• Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility: Store away from oxidizing agents.

• Specific end use(s) No relevant information available.

Control parar	vith limit values that require monitoring at the workplace:
67-56-1 Methar	
PEL (USA)	Long-term value: 260 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
TLV (USA)	Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm Skin; BEI
EL (Canada)	Short-term value: 250 ppm Long-term value: 200 ppm Skin
EV (Canada)	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
LMPE (Mexico)	Short-term value: 250 ppm Long-term value: 200 ppm PIEL, IBE

Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 25, 2019

(Cont'd. on page 6)

	(Cont'd. of pag
BEI (USA) 15 mg/L	
Medium: urine Time: end of shift	
	ackground, nonspecific)
· Exposure controls	
· General protective and hygienic i	measures:
Keep away from foodstuffs, beverage	
Immediately remove all soiled and o	contaminated clothing.
Wash hands before breaks and at t	
Avoid contact with the eyes and skin	n.
• Engineering controls:	
Keep container tightly closed.	net static discharge
Take precautionary measures agair • Breathing equipment:	not static uischalge.
Not required under normal condition	ns of use.
	device in case of insufficient ventilation.
For large spills, respiratory protection	
Protection of hands:	
Protective gloves	
The glove material has to be imperr	meable and resistant to the product/ the substance/ the preparation.
Safety glasses	
• Body protection: Protective work of	clothing
	exposure into the environment
Avoid release to the environment.	-
Risk management measures N	No relevant information available.
9 Physical and chemical prop	perties
[·] Information on basic physical	and chemical properties
· Appearance:	
Form:	Gel.
Color:	Blue
· Odor:	Alcohol-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
 pH-value: Melting point/Melting range: Boiling point/Boiling range: 	Not determined. Not determined. Not determined.

Not applicable.

Highly flammable.

· Flash point:

· Flammability (solid, gaseous):

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 25, 2019

de name: Gel Chafing Fuel	
	(Cont'd. of page
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
Oxidizing properties:	Non-oxidizing.
Vapor pressure:	Not determined.
Density:	
Relative density:	Not determined.
Vapor density:	Not applicable.
Evaporation rate:	Not applicable.
Solubility in / Miscibility with	
Water:	Soluble.
Partition coefficient (n-octanol/w	rater): Not determined.
Viscosity	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
Other information	No relevant information available.

10 Stability and reactivity

· Reactivity: No relevant information available.

· Chemical stability:

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

[•] Possibility of hazardous reactions

Used empty containers may contain product gases which form explosive mixtures with air.

- Reacts with oxidizing agents.
- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers

· Hazardous decomposition products Carbon monoxide and carbon dioxide

11 Toxicological information

[·] Information on toxicological effects

· Acute toxicity: Toxic if swallowed, in contact with skin or if inhaled.

- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Irritating effect.

(Cont'd. on page 7)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 25, 2019

Trade name: Gel Chafing Fuel

(Cont'd. of page 6)

· Sensitization: No sensitizing effects known.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

• NTP (National Toxicology Program):

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

• Germ cell mutagenicity: Based on available data, the classification criteria are not met.

· Carcinogenicity: Based on available data, the classification criteria are not met.

• **Reproductive toxicity:** Based on available data, the classification criteria are not met.

• STOT-single exposure: Causes damage to the central nervous system and optic nerve.

· STOT-repeated exposure: Based on available data, the classification criteria are not met.

• Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

[·] Toxicity

· Aquatic toxicity No relevant information available.

· Persistence and degradability Biodegradable.

• Other information: The product is biodegradable.

· Bioaccumulative potential: Does not accumulate in organisms

• Mobility in soil: No relevant information available.

· Other adverse effects No relevant information available.

13 Disposal considerations

[•] Waste treatment methods

· Recommendation:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

[·] Uncleaned packagings

• Recommendation: Disposal must be made according to official regulations.

· Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

[·] UN-Number

· DOT

UN1325

(Cont'd. on page 8)

Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 25, 2019

Trade name: Gel Chafing Fuel

	(Cont'd. of page
ADR/RID/ADN, IMDG, IATA	UN2926
UN proper shipping name DOT ADR/RID/ADN, IMDG IATA	Flammable solid, organic, n.o.s. (methanol) FLAMMABLE SOLID, TOXIC, ORGANIC, N.O. (METHANOL) Flammable solid, toxic, organic, n.o.s. (methanol)
Transport hazard class(es)	
DOT	
Class	4.1
Label	4.1
ADR/RID/ADN	
Class	4.1 (FT1)
Label	4.1+6.1
IMDG	
Class	4.1
Label	4.1/6.1
Class	4.1
Label	4.1 (6.1)
Packing group DOT, ADR/RID/ADN, IMDG, IATA	II
Environmental hazards Marine pollutant:	No
Special precautions for user	Warning: Flammable solids, self-reactive substanc
Danger code (Kemler):	and solid desensitised explosives 46
EMS Number:	F-A,S-G

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 25, 2019

	(Cont'd.	of pag
	oort in bulk according to Annex II of OL73/78 and the IBC Code Not applicable.	
[.] Transp	oort/Additional information:	
DOT		
\diamondsuit	Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 kg	each
· ADR/RI	D/ADN	
\diamondsuit	Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 kg	each
·IMDG		
\diamondsuit	Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 kg	each
· IATA		
Ŷ	Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 I 1 kg net.	kg ea
·		

Safety, health and environmental regulations/legislation specific for the substance or mixture
United States (USA)
SARA
Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

67-56-1 Methanol

• TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

· Proposition 65 (California)

 $^{\cdot}$ Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

(Cont'd. on page 10)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 25, 2019

Trade name: Gel Chafing Fuel

(Cont'd. of page 9)

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

67-56-1 Methanol

• EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

Canadian Domestic Substances List (DSL): (Substances not listed.)

67-56-1 Methanol

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent OSHA: Occupational Safety & Health Administration Flam. Liq. 2: Flammable liquids – Category 2 Flam. Sol. 1: Flammable solids – Category 1 Acute Tox. 3: Acute toxicity - Category 3 Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B STOT SE 1: Specific target organ toxicity (single exposure) - Category 1 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com