

# SAFETY DATA SHEET

Easy-Off Heavy Duty Oven and Grill Cleaner



HEALTH • HYGIENE • HOME

## 1. Product and company identification

**Product name** : Easy-Off Heavy Duty Oven and Grill Cleaner

**Supplier** : Reckitt Benckiser (Canada) Inc.  
1680 Tech Avenue, Unit #2  
Mississauga, Ontario L4W 5S9  
CANADA  
Telephone: +1 905 283 7000

**Material uses** : Oven Cleaner

**Product use** : Consumer

**SDS #** : 364200PSDS v5.0\_Canada

**Formulation #:** : 367270 v4.0

**UPC Code / Sizes** : 62200-00400 (400 gm Aerosol Can) 62200 00392 (600gm Aerosol Can)

**Manufacturer** : Reckitt Benckiser LLC.  
Morris Corporate Center IV  
399 Interpace Parkway (P.O. Box 225)  
Parsippany, New Jersey 07054-0225  
+1 973 404 2600

**Validation date** : 09/06/2015.

**Emergency telephone number** : 1-800-338-6167

**Transport Emergency phone:** : 1-800-424-9300 (U.S. & Canada) CHEMTREC  
Outside U.S. and Canada (North America), call Chemtrec:703-527-3887

## 2. Hazards identification

### Emergency overview

**Physical state** : Liquid. [Liquefied compressed gas.]

**Color** : Tan.

**Odor** : Lemon-like.

**Signal word** : DANGER

**Hazard statements** : CORROSIVE CONTENTS UNDER PRESSURE  
CONTAINER MAY EXPLODE IF HEATED CAUSES BURNS DANGEROUS FUMES  
FORM WHEN MIXED WITH OTHER PRODUCTS

**Precautionary measures** : Do not puncture. Do not burn. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes.

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Potential acute health effects**

**Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

**Ingestion** : Harmful if swallowed.

## 2. Hazards identification

- Skin** : Severely irritating to the skin.
- Eyes** : Severely irritating to eyes. Risk of serious damage to eyes.

### Potential chronic health effects

- Chronic effects** : Contains material that may cause target organ damage, based on animal data.
- Target organs** : Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, liver, heart, gastrointestinal tract, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea, testes.

### Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin** : Adverse symptoms may include the following:  
irritation  
redness
- Eyes** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

- Medical conditions aggravated by over-exposure** : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

## 3. Composition/information on ingredients

Name	CAS number	%
Sodium hydroxide	1310-73-2	2.5 - 5
n-butane	106-97-8	2.5 - 5
(2-(2-butoxyethoxy)ethanol) Diethylene glycol monobutyl ether	112-34-5	2.5 - 5
2-aminoethanol	141-43-5	2.5 - 5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

## 4. First aid measures

- First aid** : If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.
- Protection of first-aiders** : Use personal protective equipment as required.
- Notes to physician** : Treat symptomatically.

## 5. Fire-fighting measures

**Flammability Remark** : Not available.

**Explosibility Remark** : Not available.

**Flammability of the product** In a fire or if heated, a pressure increase will occur and the container may burst. Bursting aerosol containers may be propelled from a fire at high speed.

### Extinguishing media

**Suitable** Use an extinguishing agent suitable for the surrounding fire.

**Not suitable** None known.

### Special hazards arising from the substance or mixture

**Special exposure hazards** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Hazardous thermal decomposition products** Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
metal oxide/oxides

**Fire or projection hazard.** Aerosol cans may explode with extreme heat and become projectiles.

### Advice for firefighters

**Special protective equipment for fire-fighters** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Special remarks on explosion hazards

**Sensitivity to mechanical impact** Not available.

**Sensitivity to static discharge** Not available.

## 6. Accidental release measures

**Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods for cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## 6. Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## 7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Empty containers retain product residue and can be hazardous.

Do not puncture or incinerate CONTENTS UNDER PRESSURE

- Storage** : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Use appropriate containment to avoid environmental contamination.

CONTAINERS SHOULD BE KEPT OUT OF REACH OF CHILDREN. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn after use. Keep away from all sources of ignition. Fires involving flammable aerosols are severe and can spread very quickly. Warehouses and stores containing aerosols should therefore be separated from other areas by a fire resistant construction of at least one half hour duration. Stores should be well ventilated, particularly at low levels. The natural ventilation in a large open warehouse building will normally be suitable. Avoid the storage of aerosols in basements where practicable.

## 8. Exposure controls/personal protection

<u>Occupational exposure limits</u>		TWA (8 hours)			STEL (15 mins)			Ceiling (ACGIH TLV)			Notations
Ingredient	List name	ppm	mg/m <sup>3</sup>	Other	ppm	mg/m <sup>3</sup>	Other	ppm	mg/m <sup>3</sup>	Other	
butane	US ACGIH 6/2013	-	-	-	1000	-	-	-	-	-	
	AB 4/2009	1000	-	-	-	-	-	-	-	-	
	BC 7/2013	600	-	-	750	-	-	-	-	-	
	ON 1/2013	800	-	-	-	-	-	-	-	-	
	QC 12/2012	800	1900	-	-	-	-	-	-	-	
2-aminoethanol	US ACGIH 4/2014	3	7.5	-	6	15	-	-	-	-	
	AB 4/2009	3	7.5	-	6	15	-	-	-	-	[3]
	BC 4/2014	3	-	-	6	-	-	-	-	-	
	ON 1/2013	3	7.5	-	6	15	-	-	-	-	
	QC 1/2014	3	7.5	-	6	15	-	-	-	-	
2-(2-butoxyethoxy)ethanol	US ACGIH 4/2014	10	-	-	-	-	-	-	-	-	[a]
sodium hydroxide	US ACGIH 6/2013	-	-	-	-	-	-	-	2	-	

## 8. Exposure controls/personal protection

	AB 4/2009	-	-	-	-	-	-	-	2	-	[3]
	BC 7/2013	-	-	-	-	-	-	-	2	-	
	ON 1/2013	-	-	-	-	-	-	-	2	-	
	QC 12/2012	-	-	-	-	2	-	-	-	-	

[3]Skin sensitization

Form: [a]Inhalable fraction and vapor

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### Manufacturer: Exposure controls

**Engineering measures** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Personal protection

**Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Other protection** : Not available.

## 9. Physical and chemical properties

<b>Physical state</b>	: Liquid. [Liquefied compressed gas.]
<b>Flash point</b>	: Not available.
<b>Burning time</b>	: Not applicable.
<b>Burning rate</b>	: Not applicable.
<b>Auto-ignition temperature</b>	: Not available.
<b>Flammable limits</b>	: Not available.
<b>Color</b>	: Tan.
<b>Odor</b>	: Lemon-like.
<b>Taste</b>	: Not available.
<b>Molecular weight</b>	: Not applicable.
<b>Molecular formula</b>	: Not applicable.
<b>pH</b>	: 13.3 [Conc. (% w/w): 100%]
<b>Boiling/condensation point</b>	: Not available.
<b>Melting/freezing point</b>	: Not available.
<b>Critical temperature</b>	: Not available.
<b>Relative density (g/ml)</b>	: 0.963 to 1.177
<b>Bulk density</b>	: Not available.
<b>Vapor pressure</b>	: Not available.
<b>Vapor density</b>	: Not available.
<b>Volatility</b>	: Not available.
<b>Odor threshold</b>	: Not available.
<b>Evaporation rate</b>	: Not available.
<b>SADT</b>	: Not available.
<b>Viscosity</b>	: Not available.
<b>Ionicity (in water)</b>	: Not available.
<b>Dispersibility properties</b>	: Not available.
<b>Solubility</b>	: Easily soluble in the following materials: cold water and hot water.
<b>Physical/chemical properties comments</b>	: Not available.
<b><u>Aerosol product</u></b>	
<b>Type of aerosol</b>	: Spray
<b>Heat of combustion</b>	: 3.817 kJ/g

## 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: The product is stable.
<b>Conditions to avoid</b>	: No specific data. Keep away from extreme heat. Protect from moisture. Keep from freezing. Do not store above 50°C
<b>Incompatible materials</b>	: No specific data.
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

364200PSDS v5.0\_Canada

## 10. Stability and reactivity

**Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

## 11. Toxicological information

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
butane	LC50 Inhalation Vapor	Rat	658000 mg/m <sup>3</sup>	4 hours
2-aminoethanol	LD50 Oral	Rat	1720 mg/kg	-
2-(2-butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-

**Conclusion/Summary** : Not available.

### Chronic toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

**Conclusion/Summary** : Not available.

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-aminoethanol	Eyes - Severe irritant	Rabbit	-	250 Micrograms	-
	Skin - Moderate irritant	Rabbit	-	505 milligrams	-
2-(2-butoxyethoxy)ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
sodium hydroxide	Eyes - Severe irritant	Rabbit	-	20 milligrams	-
	Eyes - Severe irritant	Monkey	-	24 hours 1 Percent	-
	Eyes - Mild irritant	Rabbit	-	400 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	24 hours 50 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	1 Percent	-
	Eyes - Severe irritant	Rabbit	-	0.5 minutes 1 milligrams	-
	Skin - Mild irritant	Human	-	24 hours 2 Percent	-
	Skin - Severe irritant	Rabbit	-	24 hours 500 milligrams	-

**Conclusion/Summary** : Not available.

**Skin** : Not available.

**Eyes** : Not available.

**Respiratory** : Not available.

### Sensitizer

Product/ingredient name	Route of exposure	Species	Result
Not available.			

**Conclusion/Summary** : Not available.

**Skin** : Not available.

## 11. Toxicological information

**Respiratory** : Not available.

### Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

**Conclusion/Summary** : Not available.

### Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Not available.						

### Mutagenicity

Product/ingredient name	Test	Experiment	Result
Not available.			

**Conclusion/Summary** : Not available.

### Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

**Conclusion/Summary** : Not available.

### Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Not available.						

**Conclusion/Summary** : Not available.

## 12. Ecological information

**Ecotoxicity** : No known significant effects or critical hazards.

### Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
2-aminoethanol	Acute EC50 8.42 mg/l Fresh water	Algae - Desmodesmus subspicatus	72 hours
	Acute LC50 >100000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
2-(2-butoxyethoxy)ethanol	Acute LC50 170000 µg/l Fresh water	Fish - Carassius auratus	96 hours
	Acute LC50 1300000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours

**Conclusion/Summary** : Not available.

### Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Not available.				

**Conclusion/Summary** : Not available.

**Partition coefficient: n-octanol/water** : Not available.

**Bioconcentration factor** : Not available.

**Mobility** : Not available.

## 12. Ecological information

**Toxicity of the products of biodegradation** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

Release of large quantities into water may cause a pH-change resulting in danger for aquatic life.







## 13. Disposal considerations

**Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14. Transport information

For long distance transport of bulk material or shrunk pallet take into consideration sections 7 and 10.

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>DOT Classification</b>	UN1950	Aerosols, flammable	2.1 (8)	-		<u>Limited quantity</u>
<b>TDG Classification</b>	UN1950	Aerosols, flammable	2.1 (8)	-		<u>Limited quantity</u>
<b>Mexico Classification</b>	UN1950	Aerosols, flammable	2.1 (8)	-		<u>Limited quantity</u>
<b>IMDG Class</b>	UN1950	Aerosols, flammable	2.1 (8)	-		<u>Limited quantity</u>
<b>IATA-DGR Class</b>	UN1950	AEROSOLS, flammable, containing substances in Class 8 packing group II	2.1 (8)	-	 	<u>See DG List.</u>

PG\* : Packing group

## 15. Regulatory information

### United States

**U.S. Federal regulations** : TSCA 8(a) PAIR: 7-hydroxycitronellal  
**SARA 302/304**: No products were found.  
**SARA 311/312 Hazards identification**: Immediate (acute) health hazard, Delayed (chronic) health hazard  
**Clean Water Act (CWA) 311**: sodium hydroxide  
**Clean Air Act (CAA) 112 regulated flammable substances**: butane

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

### SARA 311/312 HCS 1994

**Classification** : Immediate (acute) health hazard  
 Delayed (chronic) health hazard

### Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
butane	2.5 - 5	Yes.	Yes.	No.	No.	Yes.
2-aminoethanol	2.5 - 5	Yes.	No.	No.	Yes.	Yes.
2-(2-butoxyethoxy)ethanol	2.5 - 5	Yes.	No.	No.	Yes.	Yes.
sodium hydroxide	2.5 - 5	No.	No.	No.	Yes.	Yes.

### SARA 313

	Product name	CAS number	Concentration
<b>Form R - Reporting requirements</b>	2-(2-butoxyethoxy)ethanol	112-34-5	4.75
<b>Supplier notification</b>	2-(2-butoxyethoxy)ethanol	112-34-5	4.75

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

### State regulations

**Massachusetts** : The following components are listed: ETHANOLAMINE; SODIUM HYDROXIDE; BUTANE

**New York** : The following components are listed: Sodium hydroxide

**New Jersey** : The following components are listed: ETHANOLAMINE; ETHANOL, 2-AMINO-; GLYCOL ETHERS; SODIUM HYDROXIDE; CAUSTIC SODA; BUTANE

**Pennsylvania** : The following components are listed: ETHANOL, 2-AMINO-; GLYCOL ETHERS; SODIUM HYDROXIDE (NA(OH)); BUTANE

## 15. Regulatory information

### Canada

**WHMIS (Canada)** : Class B-5: Flammable aerosol.  
Class E: Corrosive material

### Canadian lists

**Canadian NPRI** : The following components are listed: Diethylene glycol butyl ether; Butane (all isomers)

**CEPA Toxic substances** : None of the components are listed.

**Canada inventory** : Not determined.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

## 16. Other information

**Hazardous Material Information System (U.S.A.)** :

Health	3
Flammability	1
Physical hazards	0
Personal protection	D

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**National Fire Protection Association (U.S.A.)** :



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

**Date of issue** : 09/06/2015.

**Date of previous issue** : 24/02/2009

**Version** : 5

364200PSDS v5.0\_Canada

## 16. Other information

**Prepared by** : Reckitt Benckiser LLC.  
Product Safety Department  
1 Philips Parkway  
Montvale, New Jersey 07646-1810 USA.  
FAX: 201-476-7770

**Revision comments** : Update as per US GHS

☑ Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.