



Isotope® ANSI CE CSA BALLISTIC



DIELECTRIC



RUBBER NOSEPIECE



INCLUDES STRAP



ADJUSTABLE TEMPLES

Dielectric

Interchangeable temples and neoprene strap

Temples adjust to three different lengths

Dual frame design features a rubber gasket

Passes MIL-PRF 32432 High Velocity Impact Standards

Passes D3: Droplet and Splash Test when worn with strap

Part No.	Black Frame
GB9410STM ●●●●	AF Clear H2MAX
GB9420STM ●●●●	AF Gray H2MAX
GB9430STM ●●●●	AF Amber H2MAX
GB9480ST ●●●●	AF I/O Mirror



H2MAX
ANTI-FOG

vimeo.com/pyramex/h2max

Watch the video
vimeo.com/pyramex/isotope

Download a FREE QR Reader to your smartphone through your phone's app store

Scan the code

There's more to see at
PYRAMEXSAFETY.COM
(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ (●) and Canadian (CSA Z94.3) (●) standards. All lenses are hard coated polycarbonate scratch-resistant and provide 99% protection from harmful UV rays. Some options meet European (EN166) (●), or Ballistic (MIL-PRF-32432) (●) standards.



Isotope®

General Specifications

Weight: 41 gm spectacle | 40.68 gm goggle
 PD: 64 mm
 Bridge: 11.7 mm
 Lens base: 9.5 curve
 Lens size diagonal: 74.7 mm
 Lens size vertical: 45 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 163 - 173 mm spectacle | 73 mm goggle
 Overall width (hinge - hinge): 134 mm
 Closest point between temple tips: 65 mm
 Closest point between strap holding parts: 137 mm
 Closest point between lens: 13 mm
 Strap Length: 192 mm spectacle | 520 mm goggle

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Gasket: polycarbonate and thermoplastic elastomers (TPE)
 Temple: polycarbonate
 Temple tips: polycarbonate and thermoplastic elastomers (TPE)
 Temple strap: polyester
 Goggle strap: neoprene
 Goggle strap holder: polycarbonate
 Strap takeup loop: nylon
 Sleeve: polycarbonate
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Frame Marking
GB9410STM	P Z87 + U6	P Z87 + D3 / P c SEI CAN/CSA Z94.3-15
GB9420STM	P Z87 + U6 L2.5	P Z87 + D3 / P c SEI CAN/CSA Z94.3-15
GB9430STM	P Z87 + U6	P Z87 + D3 / P c SEI CAN/CSA Z94.3-15
GB9480ST	P Z87 + U6 L1.7	P Z87 + D3 / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 D3: Droplet & Splash Test with strap
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967