# Force R Sporty dual lens design





- Sporty, lightweight design eliminates the bulkiness and weight of a goggle.
- Quick Release Interchangeable Temples and Strap.
- Vented foam carriage provides maximum dust protection, as well as sufficient airflow outlet for heat.
- Dual pane lens provides the ultimate anti-fog performance by isolating the temperature difference inside and outside of this eyewear, provides 99.9% protection against harmful UV rays.
- Outer polycarbonate lens protects against the environment, while inner acetate lens is designed to prevent fogging. The thermal system provides anti-fog protection in the worst weather conditions or extreme-temperature working environments.
- Outside lens is coated with H2X™ Anti-fog Technology for even more resistance to fogging, due to extreme temperatures.
- Passes MIL-PRF 32432 High Velocity Impact Standards.

GENERAL SPECIFICATION
Bridge: 14.5mm
Closest Point Between Lens: 16mm
Closest Point Between Strap Holding Parts: Temples 148mm (98mm) / Strap Length 360mm
Lens Base: 8 Curve
Lens Size Diagonal: 72mm
Lens Size Vertical: 51mm
Lens Thickness: 1.8mm
Overall Length (Lens-Tip): 165mm
Overall Width: 165mm
PD: 68mm
Weight: 47gm (Goggles) 48gm (Spectacle)



PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 144 pcs

COMPONENT	MATERIAL	FEATURES		
Foam	CR Foam	Flexible material with cushion provides the top protection from dust & flying		
Nose Piece	CR Foam	particles with the best fitting & comfort		
Front Carriage	Nylon	Vented structure with front frame for adapting foam		
Foam Frame	Nylon	Dual frame style with extended side protection		
Goggle Strap	Polyester	Adjustable textile elastic fixed on strap holders with quick release part		
Temple Strap	Polyester			
Goggle Strap Holder	POM (Polyethylene)	Sewed with wide strap		
Hinge	Polycarbonate	2 in 1 design; hinges are pin-insert style, integral with angle adjustable structure		
Ratchet	Polycarbonate			
Lens	Polycarbonate (Front Lens)	8 base dual pane lens (polycarbonate-HC lens on the outer side with acetate-AF lens on inner side)		
	Acetate (Inner Lens)			
	PU Foam			
Temple	Polycarbonate	Straight side sports style		
Temple Strap Holder	Nylon	Sewed with thin strap		
Temple Tip	Nylon	Soft & flat without pressure		

PART	LENS	LENS MARKING	FRAME MARKING
SB7010SDT	Clear H2X Anti-Fog	P Z87 + U6 L1.3	P Z 87 + / P c SEI CAN/CSA Z 94.3-07
SB7020SDT	Gray H2X Anti-Fog	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB7025SDT	Light Gray H2X Anti-Fog	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB7030SDT	Amber H2X Anti-Fog	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB7070SDT	Silver Mirror Anti-Fog	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB7080SDT	Indoor/Outdoor Mirror Anti-Fog	P Z87 + U6 L1.7	P Z 87 + / P c SEI CAN/CSA Z 94.3-07

# **LENS MARKING**

### Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

- +: High Impact
- H: Small Head Size
- S: Special Purpose

### **UV Filter Transmittance:**

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

### **Visible Light Filters:**

L1.3: 85% Max. Visible Light L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light L3: 18% Max. Visible Light

# FRAME MARKING

## Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices