



PRO:LINE

TECHNICAL DATA SHEET

Sprayway® Pro Line Dry Lubrication & Release Agent

DESCRIPTION: stops sticking and retards corrosion. This silicone spray eliminates annoying squeaks in hinges, latches, springs, etc. It leaves no greasy or oily film and is not affected by water or oil. The heat stable formula will not freeze or melt.

USES: It protects battery terminals, tools, aluminum windows and doors. An excellent release agent for plastic injection and compression moldings. Use on any surface: metal - glass - rubber - plastic - painted surfaces - fabrics.

Table with 2 columns: SPECS and values. Rows include Can Size (20 oz), Net Weight (12 oz), Shipping Weight (13 lbs), Packaged (12 cans per case), UPC Number (0 41911 00077 2), and SAP Number (1000000562).

Table with 2 columns: PHYSICAL CHARACTERISTICS and values. Rows include Color (Colorless) and Fragrance (Solvent).

Table with 2 columns: REGULATORY and values. Rows include Shelf Life (1 Year +), Recyclable Packaging (Yes), VOC Compliant CARB/OTC/Canada (Yes), Flammability (Extremely Flammable), and 24 HR. MEDICAL EMERGENCY (1-866-836-8855).

- FEATURES
• ALL PURPOSE
• FAST DRYING
• LEAVES NO GREASY OR OILY FILM
• HEAT STABLE - WILL NOT FREEZE OR MELT

WARNING: This product can expose you to chemicals including Ethyl Benzene, Benzene, which are known to the State of California to cause cancer, and Toluene, n-Hexane, Benzene which are known to the State of California to cause birth defects or other reproductive harm.. For more information go to www.P65Warnings.ca.gov.

See label side panel for First Aid and additional precautionary statements. KEEP OUT OF REACH OF CHILDREN. CONSULT SDS BEFORE USING MADE IN THE USA WITH GLOBALLY SOURCED MATERIALS



Nonfood Compounds
NF
NO FOOD CONTACT



Please recycle