

VBTPH7213216C

Hand Hot Melt, 1.6 Mil

Technical Specifications

Width (mm)	72
Length (hand, m)	132
Colour	Clear
Backing (mils / mm): BOPP	0.96 / 0.024
Adhesive	Synthetic Rubber/Resin
Total Thickness (mils / mm)	1.54 / 0.040
Adhesion to Steel (oz/in. / N/100mm)	44 / 48
Tensile Strength (lbs/in. / N/100mm)	22 / 385
Elongation (% at break)	165
Service Temp. Min / Max	30°F (-2°C) / 140°F (60°C)
Application Temp. Min / Max	54°F (12°C) / 110°F (43°C)

Description

This Utility Grade packaging tape is primarily used for carton sealing, splicing, bundling, and other lightweight packaging applications. This product has a conformable film backing coupled with a consistent pressure sensitive hot melt adhesive coating.

Performance Features

- Adheres instantly to corrugated, paper, film and a number of surfaces
- Good edge tear and split resistance.
- Aggressive high tack adhesive with excellent holding powers

125 Madill Blvd.
Mississauga, ON, L5W 0H1, Canada

© 2025 Imperial Dade Canada. All rights reserved. Victoria Bay is a registered trademark of Imperial Bag & Paper. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

TAPVBTPH7213216C0525CAEN