

VBSH31575N

Performa 3" x 1,500'

19.05 micron / 75 Gauge

Specifications and Packaging

CHARACTERISTICS

Manufacturing Process
Thickness
Colour
Film Width
Length
Rolls per Case
Net Weight Case (lb)

VALUES

Cast
19.05 micron / 75 Gauge
Clear
3"
1,500'
15
20.25

FILM PROPERTIES

Ultimate @ Break
Ultimate Force @ Break
Load Containment @ 300s
Elmendorf Tear Strenght Force
Time to Break @ Tear
Drop Time @ Tear
Puncture Force
Displacement @ Puncture
Peel Cling Force @ 50%

UNIT	NOMINAL VALUE	TOLERANCE
%	300	+/- 10%
Lbf	40	+/- 10%
Lbf	5	+/- 10%
Lbf	19	+/- 10%
Sec	40	+/- 10%
Sec	9	+/- 10%
Lbf	7	+/- 10%
Inch	2.7	+/- 10%
Lbf	0.12	+/- 10%

NOTE: The data presented above are nominal values for the product type described and must not be construed as specifications. Therefore, no guaranty expressed or implied.

125 Madill Blvd.
Mississauga, ON, L5W 0H1, Canada

© 2024 Imperial Dade Canada. All rights reserved. Victoria Bay is a registered trademark of Imperial Bag & Paper. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.
STRFILVBSH31575N0424CAEN